







See www.schoellerallibert.com for additional material like
Handling Instructions
View Video

Accessories



4410820 - RPC Lid 1212x1012x79





4436040 - Set of Feet RPC Maxilog $(2L^+2R)$



4437030 - Runner set Maxilog (3)



2316000 - Transparent Label Holder 130x100 for RPC





Schoeller Allibert

MaxiLog 1200x1000x760 - 3R, Perforated

Item:

4429600 兄ॏ

This perforated MaxiLog® with 3 runners is the all-rounder for transporting food or large volume bulk. Strong, sturdy, automation-friendly, safe and easy to clean. This MaxiLog® is specially adapted to all needs of industrial processing and food production. Efficient in return transport thanks to its stackable dimensions. Safe and secure stacking thanks to corner stacking features. Available in a solid or perforated version with either 4 feet, 2 runners or 3 runners. UN approved versions available in 11H2 and 50H for transporting dangerous goods by road, sea, and air.

Specifications

Volume:

External (LxWxH): 1200 mm x 1000 mm x 760 mm

Internal (LxWxH): 1108 mm x 908 mm x 574 mm

610 L

Weight: 35.3 kg

Max. Individual Load capacity: 450 kg

Max.Static load on bottom container in a

stack: 4500 kg

Max. Dynamic load on bottom container in a

stack: 1000 kg

Incremental stack height: 734 mm

Base type: perf

Wall type: perf , perf

Number of Skids: 3

Number of Feet: 0

Long Side Door, Short Side Door: $$0\ No\ ,0\ No$$

www.Schoellerallibert.com

Label holder long/short side:: 1, 1

Lid available: Drop on

RFID option: Yes

Material: HDPE

Temperature range: -20 °C to 40 °C

Fire retardant: No

Standard Colour: 502 Grey RAL 7040

Schoeller Allibert

4

1200 mm x 1000

mm

2254 mm

Packaging

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies.

Defore you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet. Datasheet Rigid Pallet Containers | 26-10-2022

Units/Pallet (pc):

Pallet size:

Pallet Height:

Feature and Benefits

- Outlet valve prepared 1 and 2 inch drain valves can be fitted on demand for easy emptying
- Reinforced base Computer optimised design minuses deformation under 450 kg internal load.
- Secure Stacking Corner stacking features ensure safe and secure stacking of boxes up to 4500 kg stacking load.
- Smooth and safe All surfaces easy to clean. Inner walls are smooth which makes it easy to empty; therefore suitable for deep freezing. Automation friendly Designed to be compatible with most automated handling systems and conveyor systems
- food approved manufactured from high quality plastics.
- smooth design easy to clean, less dirt traps
- washing units can be washed
- Fully recyclable at the end of its long service life Recyclable
- We grant a 2 year warranty on all purchased products 2 years warranty

www.Schoellerallibert.com
The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies.

Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.

Datasheet Rigid Pallet Containers | 26-10-2022