



Schoeller Allibert



See [www.schoellerallibert.com](http://www.schoellerallibert.com) for additional material like  
Handling  
Instructions  
View Video

## Maestro 1200x800x158 - 3R

9371000 

Strong, hygienic and safe, this Heavy Duty Maestro® pallet with 3 runners and solid top deck provides maximum safety at handling. Ideal for cleanroom applications thanks to its smooth and easy to clean design. Easy to clean thanks to its smooth design. Unique patented non-slip deck and runners version available.

## Feature and Benefits

## Specifications

## Related Products



6015830 - Pallet Cover 1205x808x94 (A1208)



9524004 - Pallet Cover 1220x813x53 (Maestro)

Temperature range:	-20 °C to 40 °C
Fire retardant:	No
Standard Colour:	626 Blue RAL 5012

## Packaging

Material:	HDPE
External (LxWxH):	1200 mm x 800 mm x 158 mm
Weight:	19 kg
Max. Individual Load capacity:	5000 kg
Max. Static load (*):	5000 kg
Max. Dynamic load (*):	1500 kg
Max Racking load (*):	1000 kg
Pallet Deck:	Solid
Number of Skids:	3
Number of Feet:	0
Antislip option:	no

Units/Pallet (pc):	10
Pallet size:	1200 mm x 800 mm
Pallet Height:	1600 mm



Schoeller Allibert

---

RFID option: Yes

- sustainable - made from 100% sustainable materials
- 4 way for entry - Pallet jack accessible from 4 directions
- versatile - available in multiple top deck and runner configurations
- 100% plastics - no metal parts involved, easy to recycle
- Heavy duty - capable of taking heavy loads in rack
- rackable - asset can be racked and is tested according to ISO8611.
- washing - units can be washed

(\* All available technical data are the result of tests under specific conditions like temperature, type of load and testing time, based on testing procedures according to ISO8611-1:2012. In circumstances outside the ISO8611 standard our service team is available to test products according to your specific requirements and applications. Description of the specified loads are as follows:

STATIC LOAD : resistance to a pressure on a product standing on a flat ground surface under a static load according to ISO8611-1:2012, test 4 DYNAMIC

LOAD: load capability under forklift handling conditions according to ISO8611-1:2012, test 2.

RACKING LOAD: load capacity under rack conditions according to ISO8611-1:2012, test 1. When the pallet has only 3 runners, the racking is only allowed over the longside.

[www.Schoellerallibert.com](http://www.Schoellerallibert.com)

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies.

Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.

Datasheet Pallets | 25-04-2022

- Reinforced - reinforced version available, steel tubes
- Alligrip? - antislip deck version available upon demand
- SmartLink ready - Features locations for RFID and IoT beacons to ensure efficient track & tracing.
- Fully recyclable at the end of its long service life - Recyclable
- We grant a 2 year warranty on all purchased products - 2 years warranty

[www.Schoellerallibert.com](http://www.Schoellerallibert.com)

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies. Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.

Datasheet Pallets | 25-04-2022