



See [www.schoellerallibert.com](http://www.schoellerallibert.com) for additional material like  
Handling Instructions  
View Video



Schoeller Allibert

9378V00



This food-safe medium-duty 1200x800 BiPP pallet has 3 runners and a ventilated deck. The safety rim ensures that the goods remain securely in place and provides stability when stacked.

## Related Products



9366000 - Pallet Cover 1220x813x53 (Packpal®)



9366005 - Pallet Cover 1220x813x53 (Packpal®) - straps

## Specifications

External (LxWxH):	1200 mm x 800 mm x 172 mm
Internal (LxWxH):	1190 mm x 790 mm x 7 mm
Weight:	7.8 kg
Max. Individual Load capacity:	1500 kg
Max. Static load (*):	1500 kg
Max. Dynamic load (*):	1000 kg
Max Racking load (*):	500 kg
Number of Skids:	3
Antislip option:	No
RFID option:	No
Material:	HDPE
Temperature range:	-20 °C to 30 °C
Fire retardant:	No
Standard Colour:	801 Red Brown RAL 3011

## Packaging

Units/Pallet (pc):	12
Pallet size:	1200 mm x 800 mm
Pallet Height:	2137 mm

## Feature and Benefits

### BiPP Medium Including Packpal® 1200x800x172

l  
t  
e  
m  
:

- sustainable - made from 100% sustainable materials
- 4 way for entry - Pallet jack accessible from 4 directions
- versatile - available in multiple top deck and runner configurations



Schoeller Allibert

- 100% plastics - no metal parts involved, easy to recycle
- Nestable - when empty, pallet can be nested, saving space during storage and transport
- washing - units can be washed
- light - light design with maximum performance
- We grant a 2 year warranty on all purchased products - 2 years warranty

(\*) All available technical data are the result of tests under specific conditions like temperature, type of load and testing time, based on testing procedures according to ISO8611-1:2012. In circumstances outside the ISO8611 standard our service team is available to test products according to your specific requirements and applications. Description of the specified loads are as follows:

STATIC LOAD : resistance to a pressure on a product standing on a flat ground surface under a static load according to ISO8611-1:2012, test 4

DYNAMIC LOAD: load capability under forklift handling conditions according to ISO8611-1:2012, test 2.

RACKING LOAD: load capacity under rack conditions according to ISO8611-1:2012, test 1. When the pallet has only 3 runners, the racking is only allowed over the longside.

[www.Schoellerallibert.com](http://www.Schoellerallibert.com)

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies.

Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.

Datasheet Pallets | 27-10-2022

- Fully recyclable at the end of its long service life - Recyclable

[www.Schoellerallibert.com](http://www.Schoellerallibert.com)

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies. Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.