




Schoeller Allibert



See www.schoellerallibert.com for additional material like
Handling Instructions
View Video

Related Products



9366000 - Pallet Cover 1220x813x53 (Packpal®)

Eco Packpal® 1200x800x147 - 9F, Perforated

Item: 9380002

Our Packpal® range is available in 2 footprints, 1208 and 1210 with a ventilated or solid deck. Bases are available with 9 feet, 3 or even 6 runners, and can be used in all industries and for many end uses. The safety rim ensures that the goods remain securely in place and provides stability when stacked. High logistics savings thanks to its nestable design, 44 pieces per stack fit into an FTL. This version is made out of 100% recycled materials.

Specifications

External (LxWxH):	1200 mm x 800 mm x 147 mm
Internal (LxWxH):	1190 mm x 790 mm x 7 mm
Weight:	6.15 kg
Max. Individual Load capacity:	1000 kg
Max. Static load (*):	1000 kg
Max. Dynamic load (*):	600 kg
Nesting ratio (%):	63 %
Pallet Deck:	Perforated
Number of Feet:	9
Antislip option:	No
RFID option:	No
Material:	PER

Feature and Benefits

Temperature range: -18 °C to 30 °C
Fire retardant: No
Standard Colour: 090 Black Eco Packpal



Schoeller Allibert

1200 mm x 800 mm

Packaging

		Pallet size:	
Units/Pallet (pc):	44	Pallet Height:	2512 mm

- sustainable - made from 100% sustainable materials
- 4 way for entry - Pallet jack accessible from 4 directions
- versatile - available in multiple top deck and runner configurations
- 100% plastics - no metal parts involved, easy to recycle
- Nestable - when empty, pallet can be nested, saving space during storage and transport

(*) All available technical data are the result of tests under specific conditions like temperature, type of load and testing time, based on testing procedures according to ISO8611-1:2012. In circumstances outside the ISO8611 standard our service team is available to test products according to your specific requirements and applications. Description of the specified loads are as follows:

STATIC LOAD : resistance to a pressure on a product standing on a flat ground surface under a static load according to ISO8611-1:2012, test 4

DYNAMIC LOAD: load capability under forklift handling conditions according to ISO8611-1:2012, test 2.

RACKING LOAD: load capacity under rack conditions according to ISO8611-1:2012, test 1. When the pallet has only 3 runners, the racking is only allowed over the longside.

www.Schoellerallibert.com

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies.

Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.

Datasheet Pallets | 27-10-2022

- washing - units can be washed
- light - light design with maximum performance
- We grant a 2 year warranty on all purchased products - 2 years warranty
- Fully recyclable at the end of its long service life - Recyclable

www.Schoellerallibert.com

The information on this datasheet has been compiled with the greatest possible care. Nevertheless, the information provided may contain inaccuracies. Before you rely on the information provided, it must be confirmed in another way. Schoeller Allibert is not liable for any damage that occurs directly or indirectly as a result of relying on incorrect information in this datasheet.